

Government of the Peoples Republic of Bangladesh Quality Control & Training Division, BRRL

DATA & REPORT SHEET

Memo No: LAB-25-05-19-03778-001-01 Date: 2025-05-19

Client : Munshiganj Road Dvision Lab Register No. : 104 (B) 2024-2025.

Tender No. : 450528 Contract No. : NRC(e-GP)01/Dev/2019-2020

Tracking Number : LAB-25-05-19-03778 Sample Sent By : Client

Project/Work Name : Construction & Widening of Road Embankment, Construction of new Pavement, Widening & Strengthening

of existing Pavement, DBS Wearing Course at different portion of Ch. 0+000 to ch. 8+700 and 8 Nos RCC

Box Culvert at different Km (Ch. 2+697, 3+352, 4+032,

Sample Collection From: From Stackyard Sample Source: Nill

Sample Sealing Status : Sealed Sample Collected By : EE (RHD)

Name of Test : BITUMEN ROUTINE TEST

Item Name : Others Test Code : BRRL

Test Method : ASTM

Associated Agency : National Development Engineers Ltd. – Rana Builders (Pvt) Ltd. – M/S Sagar Builders JV, House #20A,

Road #44, Gulshan-2, Dhaka-1212.

Date of sample receive :

Sample Description

14/05/2025

Date of Test

: 15/05/2025

at Lab

Sample was supplied to the laboratory by Contractor's representative. Sample was carried in a pot. Amount of sample received is 7 kg approximately. Sample was sealed by Executive Engineer, RHD, Munshiganj

Road Division.

Test Performed By : Akram Hossen

Test Supervised By

Sheikh Nafiur Nur Mousum

Assistant Research Officer

BITUMEN ROUTINE TEST

Name of the test	Unit	Result	Comments	Test Code	Spec 60/70	Spec 80/100
Penetration @25°C (100g, 5s)	0.1mm	69		ASTM D-5	60 - 70	80/100
Softening Point	°C	48		ASTM D-36	48 - 56	45 - 52
Ductility (@25°C)	CM	100		ASTM D-113	≥ 100cm	≥ 100cm
Loss on heating	%(of wt)	0.09		ASTM D-6	≤ 0.2	≤ 0.5
Penetrating drop after heating	%	86.96		ASTM D-5&6	≥ 80	≥ 80
Flash point	°C	308		ASTM D-92	≥ 250	≥ 250
Specific Gravity @25/25°C						
Descriptions	Unit	Specimen #1	Specimen #2			
Weight of Pycnometer (+Stopper), A	gm	30.374				
Weight of Pycnometer +Water, B	gm	56.133				
Weight Pycnometer partially filled with Bitumen, C	gm	44.830				
Pycnometer+Bitmen+Water, D	gm	56.601				
Density of Water at 25 °C, G25	Kg/m ³	1000				
Temperature of Water (T); °C,	°C	25				
Density of Water at Temperature T °C(GT)	Kg/m ³	1000				
SP. Gravity=((C-A)/{(B-A)-(D-C)})*(GT/G25)		1.0335				
Specific Gravity		1.0335				

Comment: Test was performed on the basis of supplied sample.

Test Performed By

Hoor !

Akram Hossen Assistant Research Officer(AC) Quality Control & Training Division, BRRL

19-May-2025

Test Approved By

19-May-2025 Sheikh Nafiur Nur Mousum Assistant Engineer Quality Control & Training Division, BRRL Counter Signed By

19-May-2025

Jahangir Alam Sub Divisional Engineer Quality Control & Training Division, BRRL Counter Signed By

19-May-2025

Dewan Md. Abdul Kader Executive Engineer(AC) Quality Control & Training Division, BRRL

This is a auto generated report by OLTMS system.